

G5.BS Battery Simulator Series

The G5.BS series is bidirectional regenerative. It was developed specifically for the simulation of energy storage devices and batteries and is suitable for use in laboratories and on test benches. The modular and finely graded G5.BS series is characterized by highly dynamic response times and a wide current-voltage range with an auto-ranging factor 3. The power supplies are equipped with the powerful application software BatSim and reproduce the electrochemical and electrical properties of different battery types in charge and discharge mode realistically and in real time. This is done on the basis of battery models that can be configured easily and conveniently.

Device Types

Voltage V	Power kW	Current A	Height U	Order Code
0500	18	-108108	4	G5.BS.18.500.108
0500	27	-162162	7	G5.BS.27.500.162
0500	36	-216216	7	G5.BS.36.500.216
0500	54	-324324	10	G5.BS.54.500.324
01000	18	-5454	4	G5.BS.18.1000.54
01000	36	-108108	7	G5.BS.36.1000.108
01000	54	-162162	10	G5.BS.54.1000.162
01500	27	-5454	7	G5.BS.27.1500.54
01500	54	-108108	10	G5.BS.54.1500.108

Modular and Easy Scalable Systems

The output of an individual power supply is in the range from 0...18 kW to 0...2000+ kW, up to 3000 VDC. The advantageous modularity of REGATRON power supply solutions allows the system to be easily adapted to ever changing test requirements. Not only is it possible to reconfigure between parallel, series, and mixed operation, but also to expand the system with additional power supply units or to split it into smaller units.

Therefore, the purchase of a REGATRON power supply is a solid investment for the future.





Whether for single devices or powerful multi-device master-slave systems, REGATRON also offers turnkey cabinet solutions or project specific system integration according to customer specifications.



Battery Simulation Features

The G5.BS series realistically and dynamically simulates both the electro-chemical and electrical properties of a battery type in charge and discharge mode. Other features include high data resolution and options for meeting high safety standards for operators. The real-time computing process of the application software BatSim perfectly matches the internal timing of the DC power supply. Therefore, an optimum computing rate is achieved leading to very short response times even in cases of steep changes in charge/discharge currents. Each battery type reacts in a specific manner to charge and discharge currents in terms of state of charge, cell voltage, ohmic and parametric losses, and polarization effects. These dependencies are considered by specific mathematical models used in the REGATRON BatSim software/firmware. The operator can fine tune the model with several well-defined parameters to adjust the simulation to a user's requirement.

Features such as adjustable controller settings and the integrated powerful 8-channel digital scope assist the user to quickly and easily achieve optimal system behavior for a special application requirement. The G5.BS series also offers the possibility to store, edit and recall any device configuration on board the power supply.

Models of the following battery types are available for configuration: Li-ion, lead-acid, NiMH, and NiCd.

Basic Configuration			System State	
Battery model	Lilon Regatron		I_discharge	74.780 A
# cells in series	50		U_bat_out	195.51 V
# cells in parallel	4		Charge count	7.83761 Ah
State of charge	67.000	5 %	Total Capacity	14.000 Ah
Cell Cutoff limits:			5	5.042
Lower cutoff	2.80	v		1
Upper cutoff	4.25	v		·
Enable	স		Simulation Control	Script running
Cell parameters:				Simulation active
Nominal voltage	3.70	v		
Rated Q (Capacity)	3.50] Ah	Data behaviour	
Advanced	Configuration		Record 1	~

Figure 2: BATSim configuration – a few clicks away from the required battery simulation.

General Dynamic Data

I

rise/fall time	voltage 090%	150200 μs
set-value step	current -9090%	50100 μs
response time load step	CV, recovery within 0.5% set value	100150 μs

Accuracy

The G5.BS series has an exceptional accuracy of <0.02% FS. There is even an additional high-resolution current measurement range from -10 to 10% FS.

Control Modes

- CV constant voltage
- CC constant current
- CP constant power
- CR constant resistance
- Ri internal resistance simulation

System Control

BatSim	battery simulation and
	configuration software
G5.Control	operating and maintenance software
API	.NET programming, e.g., by LabView,
	Python, Matlab, or REST interface
I/O port	Analog interface for set and actual
	values, operating states

Grid Connection

The wide-band AC input accepts all common AC grid systems and has an active power factor correction.

AC Grid	380480 VAC ±10% at 50/60 Hz
PF	0.99
Efficiency	9596%



Options

Software and Control

HMI

The HMI built into the front panel allows comprehensive and convenient operation of the power supply via touch display.



Figure 3: Intuitive control by HMI touch display. Everything you need at a glance.

User Safety

- Integrated safety relay (ISR) for increased emergency stop reliability supporting performance level PL c / PL e according to EN ISO 13849
- Discharge of AC filter (XCD), recommended for mobile use of the device. XCD ensures a discharge time of the AC filter <1 s as required by EN 50178
- AC terminal protection cover (PAC.AC), recommended for use as tabletop unit

Rack-Integrated System Solutions

- Mobile rack solutions up to IP54
- Insulation monitoring: remote activation of the insulation measurement, actual insulation value and warning/error status are provided by optional HMI
- Easy reconfiguration between parallel, series, and mixed operation



Figure 4: REGATRON's rack-integrated turn-key system solutions, e.g., 72 kW (left) and 162 kW (right) power levels. Various types of AC/DC connectors and cables allow for comfortable handling. Third-party product integration and numerous safety options are additional features.

Environmental Conditions

Front-panel-mounted air filter (AirFilter), recommended for use in dusty environments.



Important Features of the G5.BS Series

Technology

- Technologically advanced, fast switching, compact 19-inch power supplies
- High control dynamics in the 100...200 µs range – even at higher power levels
- Exceptional accuracy of <0.02% FS, additional high-resolution measurement range
- Wide current-voltage range with an autoranging factor 3
- CV, CC, CP, CR, and Ri-Sim control modes
- Regenerative and highly efficient, resulting in significant reduction of energy consumption and heat dissipation

System Capability

- Modular and easy scalable systems
- Parallel, series, and mixed operation with a digital high-speed bus
- Simple master-slave configuration with the operating software
- Easy rack mounting
- Optional safety features such as 2-channel safety interface and insulation monitoring
- Turn-key cabinet solutions or project-specific system integration according to customer specification

System Control and Options

- Operating software, extended analysis, parameterization options, and calibration
- Application software with visualization, programming, and data logger
- Powerful application programming interfaces (APIs)

For detailed technical information, contact your local sales partner or Regatron.



All product specifications and information herein are provisional and subject to change without notice.

Filename: PD_G5.BS_EN_201007.docx

REGATRON DC & AC Power Supplies: Modular · Precisely Engineered · Technologically Advanced



